



ND INDUSTRIES, INC.
1893 BARRETT ROAD
TROY, MICHIGAN 48084
 (248) 288-0000 Fax: (248) 288-0022
24 hr. EMERGENCY CHEMTREC:
1-800-424-9300

PRODUCT: ND Epoxy-Lock®
MSDS ID: ND2141
ORIG. DATE: 9/21/98
REV. DATE: 1/30/06

PREPARED BY: **Chemical Safety**

SECTION I -Material Identification and Information H: 1 F: 1 R: 2 PPE C

COMPONENTS	CAS #	PERCENT %	OSHA PEL	ACGIH TLV	OTHER LIMITS RECOMMENDED
Amine curing agent adduct	UVH-01-04	unassigned	25-30	n.e.	n.e.
Dimethacrylate ester	UVH-01-122	24448-20-2	15-20	n.e.	n.e.
Amine accelerator	UVH-01-66	103-83-3	2-6	n.e.	n.e.
Phosphine oxide	UVH-01-129	75980-60-8	1-5	n.e.	n.e.
Epoxy resin	UVR-01-223	Trade secret	30-35	n.e.	n.e.
Triacrylates	UVR-01-67	15625-89-5	10-15	n.e.	n.e.

All ingredients are listed on the TSCA Inventory. n.a.= not applicable / n.e.=not established

SECTION II -Physical and Chemical Characteristics

BOILING POINT:	n.a.		VOC #/gal. :
VAPOR DENSITY:	n.a.	air = 1	DENSITY OF COATING:
VAPOR PRESSURE:	n.a.		
MELTING POINT:	n.a.		
SPECIFIC GRAVITY:	1.05	water = 1	
EVAPORATION RATE:	n.a.		
WATER REACTIVE:	No		
SOLUBILITY IN WATER:	Nil		
APPEARANCE AND ODOR:	Two stripes of solid film with slight amine odor.		

SECTION III - Fire and Explosion Hazard Data

FLASH POINT:	>200°F	Pensky Marten Closed Cup
AUTOIGNITION TEMPERATURE:	not determined	
FLAMMABILITY LIMITS % IN AIR:	LEL: n.a.	UEL: n.a.
EXTINGUISHER MEDIA:	Use dry chemicals and/or carbon dioxide.	
SPECIAL FIREFIGHTING PROCEDURES:	Wear NIOSH self-contained breathing apparatus with full face piece operated in pressure demand or other positive pressure mode when fighting fires.	
UNUSUAL FIRE HAZARDS AND CONDITIONS TO AVOID:	Potential organic toxic fumes. Combustion yields oxides of carbon and nitrogen.	

MATERIAL SAFETY DATA SHEET

PRODUCT: ND Epoxy-Lock®

Component	Oral LD50	Dermal LD50	Inhalation LC50
Amine curing agent adduct	1653 mg/Kg Rat	1350 mg/Kg Rabbit	0.5 mg/L Rat
Dimethacrylate ester	<5000 mg/Kg Rat	not determined	not determined
Amine accelerator	265 mg/Kg Rat	1660 mg/Kg Rabbit	2.06 mg/L Rat
Phosphine oxide	not determined	not determined	not determined
Epoxy resin	> 4g/kg Rabbit	6g/kg Rabbit	not determined
Triacrylates	5000 mg/Kg Rat	5200 mg/Kg Rabbit	not determined

SECTION VI - Control and Protective Measures

RESPIRATORY PROTECTION: In the applied form additional respiratory protection is not necessary. It is best to work in a well ventilated area.

PROTECTIVE GLOVES: A type of chemical resistant gloves must be used. Rubber, nitrile or neoprene are some suggested types.

EYE PROTECTION: Wear NIOSH approved safety glasses. Emergency eye wash stations should be available.

VENTILATION TO BE USED: LOCAL EXHAUST: MECHANICAL: SPECIFIC: OTHER (specify):

PROTECTIVE CLOTHING AND EQUIPMENT: Wear impervious clothing to prevent repeated or prolonged skin contact.

HYGIENIC WORK PRACTICES: Practice good personal hygiene and wash hands after using product. Adhere to work practices established by government regulations.

SECTION VII - Precautions for Safe Handling and Spill/Leak Procedures

STEPS TO BE TAKEN IF MATERIAL IS SPILLED OR RELEASED:

Sweep up material and place in proper waste receptacle.

WASTE DISPOSAL METHODS: Dispose of material in accordance with local, state and federal regulations.

SAFE HANDLING AND STORAGE: Store in a cool dry area away from direct sunlight.

OTHER PRECAUTIONS AND SPECIAL HAZARDOUS INFORMATION:

n.a.

RECOMMENDED NFPA/HMIS RATING

HEALTH 1

FLAMMABILITY 1

REACTIVITY 2

PERSONAL PROTECTION C

note: ratings may differ according to application, environment, and physical state.

MATERIAL SAFETY DATA SHEET

PRODUCT: ND Epoxy-Lock®

NOTES:

Proper DOT Shipping Name: Not Regulated

SECTION 313 SUPPLIER NOTIFICATION

Detaching this notification from the Material Safety Data Sheet is prohibited by law and any copying or distribution of same requires this attachment be included.

This product contains the following toxic chemicals subject to the reporting requirements of section 313 of the Emergency Planning and Community Right-To-Know Act of 1986 and 40 CFR 372:

<u>CAS #</u>	<u>CHEMICAL NAME</u>	<u>% BY WEIGHT</u>
--------------	----------------------	--------------------

This product contains no chemical above *de minimis* levels that is subject to Toxic Chemical Release Reporting under Section 313.

This product contains the following materials that under California Proposition 65 of the Safe Drinking Water and Toxic Enforcement Act of 1986 are recognized to cause cancer or reproductive toxicity.

<u>Material</u>	<u>CAS #</u>	<u>Concentration %</u>	<u>Cancer Agent</u>	<u>Reproductive Toxin</u>	<u>cancer agent & Reproductive Toxin</u>
Epichlorohydrin	106-89-8	§1 ppm	X		
Toluene	108-88-3	(trace)		X	
Phenyl glycidyl ether	122-60-1	<2ppm	X		

ND Epoxy-Lock® is a registered trademark of ND Industries®, Inc.

The information contained herein is based on the data available to us and is believed to be correct. However, ND Industries®, Inc. makes no warranty, expressed or implied regarding the accuracy of these data or the results to be obtained from the use thereof. Information is supplied upon the condition that the persons receiving same will make their own determination as to its suitability for their properties prior to use. Since conditions of use are beyond our control, all risks are assumed by the user.