

Safety Data Sheet acc. to OSHA HCS

Date of issue: 07/23/2026

Reviewed on 07/23/2026

1 Identification

- Product identifier

- Trade name: ST-3® Thread Sealant

- Synonyms: ST-3-L13 - Applied

- Other means of identification

- Part number: ST3L13-applied

- Application of the substance / the mixture

Sealing

Sealant

- Details of the supplier of the safety data sheet

- Manufacturer/Supplier:

ND Industries, a subsidiary of H.B. Fuller Company

1000 North Crooks Road

Clawson, MI 48017

USA

Telephone: +1-248-288-0000

Email: nd-info@hbfuller.com

Websites: www.ndindustries.com | www.vibra-tite.com

- Information department: Product Safety Department

- Emergency telephone number:

United States: 1-800-424-9300

International: +1-703-527-3887

2 Hazard(s) identification

- Classification of the substance or mixture



GHS07

Skin irritation 2 H315 Causes skin irritation.

Eye irritation 2B H320 Causes eye irritation.

- Label elements

- GHS label elements The product is classified and labeled according to the Globally Harmonized System (GHS).

- Hazard pictograms



GHS07

- Signal word Warning

- Hazard statements

H315+H320 Causes skin and eye irritation.

- Precautionary statements

P264 Wash thoroughly after handling.

P280 Wear protective gloves.

P302+P352 If on skin: Wash with plenty of water.

P321 Specific treatment (see on this label).

P305+P351+P338 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P332+P313 If skin irritation occurs: Get medical advice/attention.

P362+P364 Take off contaminated clothing and wash it before reuse.

P337+P313 If eye irritation persists: Get medical advice/attention.

- Other hazards

- Results of PBT and vPvB assessment

- PBT: Not applicable

- vPvB: Not applicable

- Classification according to (d)(1)(ii) of § 1910.1200

The SDS issuer does not object to the classifications provided by importers or manufacturers of precursor products.

(Contd. on page 2)

Safety Data Sheet

acc. to OSHA HCS

Date of issue: 07/23/2026

Reviewed on 07/23/2026

Trade name: ST-3® Thread Sealant

(Contd. of page 1)

- Hazards not otherwise classified

There are no adverse physical or health effects known that are not covered by the hazard classes of the Hazard Communications Standard.

* 3 Composition/information on ingredients

- Chemical characterization: Mixtures

- **Description:** Mixture of the substances listed below with nonhazardous additions.

- Dangerous components:

	Acrylic polymer Skin irritation 2, H315; Specific target organ toxicity (single exposure) 3, H335-H336; Eye irritation 2B, H320	10 – 30%
CAS: 1332-58-7	Kaolin	10 – 30%
CAS: 12001-26-2	Mica	7 – 13%
CAS: 13463-67-7	titanium dioxide	5 – 10%
	Acrylic polymer Eye irritation 2B, H320	1 – 5%
CAS: 112926-00-8	Precipitated silica (Silica-Amorphous) Combustible Dust	1 – 5%
CAS: 7558-79-4	Di-Sodium Phosphate Skin irritation 2, H315	0.5 – 1.5%
CAS: 8002-74-2	Paraffin wax Combustible Dust	0.5 – 1.5%
CAS: 64742-55-8	Mineral oil, light paraffinic Carcinogenicity 1B, H350	0.1 – 1%
CAS: 14808-60-7	Crystalline Silica Carcinogenicity 1A, H350; Specific target organ toxicity (repeated exposure) 1, H372	0.1 – 1%

4 First-aid measures

- Description of first aid measures

- After inhalation:

In case of unconsciousness place patient stably in side position for transportation.
Supply fresh air; consult doctor in case of complaints.

- **After skin contact:** Immediately wash with water and soap and rinse thoroughly.

- **After eye contact:** Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

- **After swallowing:** If symptoms persist consult doctor.

- **Most important symptoms and effects, both acute and delayed** No further relevant information available.

- **Indication of any immediate medical attention and special treatment needed** No further relevant information available.

5 Fire-fighting measures

- Extinguishing media

- **Suitable extinguishing agents:** Use fire fighting measures that suit the environment.

- **Special hazards arising from the substance or mixture** No further relevant information available.

- Advice for firefighters

- Protective equipment:

Wear self-contained respiratory protective device.
Wear fully protective suit.

6 Accidental release measures

- Personal precautions, protective equipment and emergency procedures

Ensure adequate ventilation
Wear protective clothing.

- Environmental precautions:

Inform respective authorities in case of seepage into water course or sewage system.
Do not allow to enter sewers/ surface or ground water.

- Methods and material for containment and cleaning up:

Dispose contaminated material as waste according to section 13.
Ensure adequate ventilation.
Dispose of the collected material according to regulations.

- Reference to other sections

See Section 7 for information on safe handling.
See Section 8 for information on personal protection equipment.
See Section 13 for disposal information.

(Contd. on page 3)

Safety Data Sheet

acc. to OSHA HCS

Date of issue: 07/23/2026

Reviewed on 07/23/2026

Trade name: ST-3® Thread Sealant

(Contd. of page 2)

7 Handling and storage

- Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace.

Open and handle receptacle with care.

Prevent formation of dust.

- **Information about protection against explosions and fires:** Keep respiratory protective device available.

- Conditions for safe storage, including any incompatibilities

- Storage:

- **Requirements to be met by storerooms and receptacles:** No special requirements.

- **Information about storage in one common storage facility:** Not required

- **Further information about storage conditions:**

Keep receptacle tightly sealed.

Store in cool, dry conditions in well sealed receptacles.

- **Specific end use(s)** No further relevant information available.

8 Exposure controls/personal protection

- Control parameters

- **Components with limit values that require monitoring at the workplace:**

At this time, the other constituents have no known exposure limits.

CAS: 1332-58-7 Kaolin

PEL Long-term value: 15* 5** mg/m³

*total dust **respirable fraction

REL Long-term value: 10* 5** mg/m³

*total dust **respirable fraction

TLV Long-term value: 2* mg/m³

E; respirable particulate matter, A4

CAS: 12001-26-2 Mica

PEL Long-term value: 20 mppcf ppm

<1% crystalline silica

REL Long-term value: 3* mg/m³

*respirable dust; containing < 1% quartz

TLV Long-term value: 0.1 mg/m³

*Respirable particulate matter

CAS: 13463-67-7 titanium dioxide

PEL Long-term value: 15* mg/m³

*total dust

REL See Pocket Guide App. A

TLV Long-term value: 0.2* 2.5** mg/m³

resp. fraction, *nanoscale, **finescale, A3

CAS: 112926-00-8 Precipitated silica (Silica-Amorphous)

PEL 20mppcf or 80mg/m³ /%SiO₂

REL Long-term value: 6 mg/m³

See Pocket Guide App. C

TLV TLV withdrawn

CAS: 8002-74-2 Paraffin wax

REL Long-term value: 2 mg/m³

TLV Long-term value: 2 mg/m³

CAS: 14808-60-7 Crystalline Silica

PEL Long-term value: 0.05* mg/m³

*resp. dust; 30mg/m³/%SiO₂+2

REL Long-term value: 0.05* mg/m³

*respirable dust; See Pocket Guide App. A

TLV Long-term value: 0.025* mg/m³

*respirable particulate matter, A2

- **Additional information:** The lists that were valid during the creation were used as basis.

- Exposure controls

- **Appropriate engineering controls** No further data; see section 7.

- **Personal protective equipment:**

- **General protective and hygienic measures:**

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing.

(Contd. on page 4)

Safety Data Sheet

acc. to OSHA HCS

Date of issue: 07/23/2026

Reviewed on 07/23/2026

Trade name: ST-3® Thread Sealant

(Contd. of page 3)

Wash hands before breaks and at the end of work.
Store protective clothing separately.
Avoid contact with the eyes and skin.

- Breathing equipment:

Not required

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.

- Protection of hands:

Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

- Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

Nitrile rubber, NBR

- Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

- Eye protection: Required use of safety glasses

- Body protection: Protective work clothing

* 9 Physical and chemical properties

- Information on basic physical and chemical properties**- General Information****- Physical state**

Solid

- Color:

White

- Odor:

Characteristic

- Odor threshold:

Not determined

- Melting point/Melting range:

Undetermined

- Boiling point/Boiling range:

≥ 100 °C (≥ 212 °F)

- Flammability:

Not determined

- Explosion limits:**- Lower:**

Not determined

- Upper:

Not determined

- Flash point:

150 °C (302 °F)

- Decomposition temperature:

Not determined

- pH-value:

Not applicable

- Viscosity:**- Kinematic:**

Not applicable

- Dynamic at 20 °C (68 °F):

1,100 mPas

- Solubility in / Miscibility with**- Water:**

Insoluble.

- Partition coefficient (n-octanol/water):

Not determined

- Vapor pressure at 20 °C (68 °F):

≤ 23.4 hPa (≤ 17.6 mm Hg)

- Vapor pressure:**- Density at 20 °C (68 °F):**~ 1.93137 g/cm³ (~ 16.11728 lbs/gal)**- Relative density**

Not determined

- Vapor density

Not applicable

- Particle characteristics

Not determined

- Other information**- Appearance:****- Form:**

Solidified mass

- Important information on protection of health and environment, and on safety.**- Ignition temperature:**

Product is not selfigniting.

- Danger of explosion:

Product does not present an explosion hazard.

- Solvent content:**- VOC content:**

0.00 %

- Solids content:

51.9 %

(Contd. on page 5)

Safety Data Sheet

acc. to OSHA HCS

Date of issue: 07/23/2026

Reviewed on 07/23/2026

Trade name: ST-3® Thread Sealant

(Contd. of page 4)

- **Change in condition**
- **Evaporation rate**

Not applicable.

10 Stability and reactivity

- **Reactivity** No further relevant information available.
- **Chemical stability**
 - **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
- **Possibility of hazardous reactions** No dangerous reactions known.
- **Conditions to avoid** No further relevant information available.
- **Incompatible materials:** No further relevant information available.
- **Hazardous decomposition products:** No dangerous decomposition products known.

*11 Toxicological information

- **Information on toxicological effects**
- **Acute toxicity:**

- **LD/LC50 values that are relevant for classification:**

Acrylic polymer

Oral	LD50	> 5,000 mg/kg (rat)
Dermal	LD50	> 5,000 mg/kg (rabbit)

CAS: 13463-67-7 titanium dioxide

Oral	LD50	> 20,000 mg/kg (rat)
Dermal	LD50	> 10,000 mg/kg (rabbit)
Inhalative	LC50/4 h	> 6.82 mg/l (rat)

Acrylic polymer

Oral	LD50	> 5,000 mg/kg (rat)
Dermal	LD50	> 5,000 mg/kg (rabbit)

CAS: 7558-79-4 Di-Sodium Phosphate

Oral	LD50	17,000 mg/kg (rat)
------	------	--------------------

- **Primary irritant effect:**

- **on the skin:** Irritant to skin and mucous membranes.
- **on the eye:** Irritating effect.

- **Sensitization:** No sensitizing effects known.

- **Additional toxicological information:**

The product shows the following dangers according to internally approved calculation methods for preparations:

Irritant

Carcinogenic.

- **Interactive effects** No interactive effects between components are known.

- **Carcinogenic categories**

- IARC (International Agency for Research on Cancer)

CAS: 13463-67-7	titanium dioxide	2B
CAS: 9002-84-0	Polytetrafluoroethylene	3
CAS: 112926-00-8	Precipitated silica (Silica-Amorphous)	3
CAS: 14808-60-7	Crystalline Silica	1

- NTP (National Toxicology Program)

CAS: 14808-60-7	Crystalline Silica	K
-----------------	--------------------	---

- OSHA-Ca (Occupational Safety & Health Administration)

None of the ingredients is listed.

- **Alternative sources for toxicological information** No non-standard sources for toxicological information where used.

12 Ecological information

- **Toxicity**
 - **Aquatic toxicity:** No further relevant information available.
- **Persistence and degradability** No further relevant information available.
- **Bioaccumulative potential** No further relevant information available.
- **Mobility in soil** No further relevant information available.
- **Results of PBT and vPvB assessment**
 - **PBT:** Not applicable
 - **vPvB:** Not applicable

(Contd. on page 6)

Safety Data Sheet

acc. to OSHA HCS

Date of issue: 07/23/2026

Reviewed on 07/23/2026

Trade name: ST-3® Thread Sealant

(Contd. of page 5)

- Other adverse effects**- Remark:** Harmful to fish**- Additional ecological information:****- General notes:**

Water hazard class 3 (Self-assessment): extremely hazardous for water

Do not allow product to reach ground water, water course or sewage system, even in small quantities.

Danger to drinking water if even extremely small quantities leak into the ground.

Harmful to aquatic organisms

13 Disposal considerations**- Waste treatment methods****- Recommendation:** Must not be disposed of together with household garbage. Do not allow product to reach sewage system.**- Uncleaned packagings:****- Recommendation:** Disposal must be made according to official regulations.**14 Transport information**

- UN-Number	
- DOT, ADN, IMDG, IATA	not regulated
- UN proper shipping name	
- DOT, ADN, IMDG, IATA	not regulated
- Transport hazard class(es)	
- DOT, ADN, IMDG, IATA	
- Class	not regulated
- Packing group	
- DOT, IMDG, IATA	not regulated
- Environmental hazards:	
- Marine pollutant:	No
- Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code	Not applicable
- Special precautions for user	Not applicable
- UN "Model Regulation":	not regulated

15 Regulatory information**- Safety, health and environmental regulations/legislation specific for the substance or mixture****- Sara****- Section 355 (extremely hazardous substances):**

None of the ingredients is listed.

- Section 313 (Specific toxic chemical listings):

None of the ingredients is listed.

- TSCA (Toxic Substances Control Act):

Acrylic polymer	ACTIVE
Kaolin	ACTIVE
Mica	ACTIVE
Polymer	ACTIVE
titanium dioxide	ACTIVE
Polytetrafluoroethylene	ACTIVE
Acrylic copolymer	ACTIVE
Sodium Aluminium silicate	ACTIVE
Di-Sodium Phosphate	ACTIVE
Paraffin wax	ACTIVE
Acrylic emulsion	ACTIVE
Mineral oil, light paraffinic	ACTIVE
Crystalline Silica	ACTIVE
Silicon dioxide, amorphous	ACTIVE
Alumina Trihydrate	ACTIVE

(Contd. on page 7)

Safety Data Sheet

acc. to OSHA HCS

Date of issue: 07/23/2026

Reviewed on 07/23/2026

Trade name: ST-3® Thread Sealant

(Contd. of page 6)

- Hazardous Air Pollutants

None of the ingredients is listed.

- Proposition 65**- Chemicals known to cause cancer:**

	Acrylic polymer
	Acrylic copolymer
CAS: 14808-60-7	Crystalline Silica

- Chemicals known to cause reproductive toxicity for females:

Acrylic copolymer

- Chemicals known to cause reproductive toxicity for males:

Acrylic copolymer

- Chemicals known to cause developmental toxicity:

Acrylic polymer
Acrylic copolymer

- Carcinogenic categories**- EPA (Environmental Protection Agency)**

None of the ingredients is listed.

- TLV (Threshold Limit Value)

CAS: 1332-58-7	Kaolin	A4
CAS: 13463-67-7	titanium dioxide	A4
CAS: 14808-60-7	Crystalline Silica	A2

- NIOSH-Ca (National Institute for Occupational Safety and Health)

CAS: 13463-67-7	titanium dioxide
CAS: 14808-60-7	Crystalline Silica

- National regulations:**- Information about limitation of use:**

Workers are not allowed to be exposed to the hazardous carcinogenic materials contained in this preparation. Exceptions can be made by the authorities in certain cases.

- Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- Department issuing SDS: H.B. Fuller Company | ND Industries Health and Environmental Affairs

- Contact: Safety, Health and Environmental Affairs

- Classification System:**- HMIS-ratings (scale 0 - 4)**

HEALTH	1	Health = *1
FIRE	1	Fire = 1
REACTIVITY	0	Reactivity = 0

- NFPA ratings (scale 0 - 4)

1	1	0	Health = 1
			Fire = 1
			Reactivity = 0

- Date of previous version 02/27/2024

- Version number of previous version: 28

- Date of preparation 07/23/2026

- Abbreviations and acronyms:

IMDG: International Maritime Code for Dangerous Goods
 DOT: US Department of Transportation
 IATA: International Air Transport Association
 EINECS: European Inventory of Existing Commercial Chemical Substances
 ELINCS: European List of Notified Chemical Substances
 CAS: Chemical Abstracts Service (division of the American Chemical Society)
 VOC: Volatile Organic Compounds (USA, EU)
 LC50: Lethal concentration, 50 percent
 LD50: Lethal dose, 50 percent
 PBT: Persistent, Bioaccumulative and Toxic
 vPvB: very Persistent and very Bioaccumulative
 NIOSH: National Institute for Occupational Safety
 OSHA: Occupational Safety & Health
 TLV: Threshold Limit Value

(Contd. on page 8)

Safety Data Sheet

acc. to OSHA HCS

Date of issue: 07/23/2026

Reviewed on 07/23/2026

Trade name: ST-3® Thread Sealant

(Contd. of page 7)

PEL: Permissible Exposure Limit
REL: Recommended Exposure Limit
Skin irritation 2: Skin corrosion/irritation – Category 2
Eye irritation 2B: Serious eye damage/eye irritation – Category 2B
Carcinogenicity 1A: Carcinogenicity – Category 1A
Carcinogenicity 1B: Carcinogenicity – Category 1B
Specific target organ toxicity (single exposure) 3: Specific target organ toxicity (single exposure) – Category 3
Specific target organ toxicity (repeated exposure) 1: Specific target organ toxicity (repeated exposure) – Category 1

- *** Data compared to the previous version altered.**

- **Disclaimer**

IMPORTANT: Information, specifications, procedures and recommendations provided ("information") are based on our experience and we believe this to be accurate. No representation, guarantee or warranty is made as to the accuracy or completeness of the information, or that use of the product will avoid losses or damages or give desired results. It is user's sole responsibility to test and determine the suitability of any product for the intended use. Tests should be repeated if materials or conditions change in any way. The user is advised to review the specific context of the intended use to determine whether the user's intended use violates any law or infringes upon any patent(s). No employee, distributor or agent has any right to change these facts and offer a guarantee of performance.

H.B. Fuller, ND, ND Industries, and Vibra-TITE are registered trademarks of the H. B. Fuller Company.