

Safety Data Sheet

acc. to OSHA HCS

Date of issue: 07/23/2026

Reviewed on 07/23/2026

1 Identification

- Product identifier

- **Trade name:** ST-3® Thread Sealant

- **Synonyms:** ST-3-W - Applied

- Other means of identification

- **Part number:** ST3W-applied

- **Application of the substance / the mixture**

Sealing

Sealant

- Details of the supplier of the safety data sheet

- Manufacturer/Supplier:

ND Industries, a subsidiary of H.B. Fuller Company

1000 North Crooks Road

Clawson, MI 48017

USA

Telephone: +1-248-288-0000

Email: nd-info@hbfuller.com

Websites: www.ndindustries.com | www.vibra-tite.com

- **Information department:** Product Safety Department

- Emergency telephone number:

United States: 1-800-424-9300

International: +1-703-527-3887

2 Hazard(s) identification

- Classification of the substance or mixture



GHS08 Health hazard

Specific target organ toxicity (repeated exposure) 2 H373 May cause damage to organs through prolonged or repeated exposure.



GHS07

Skin irritation 2

H315 Causes skin irritation.

Eye irritation 2B

H320 Causes eye irritation.

- Label elements

- **GHS label elements** The product is classified and labeled according to the Globally Harmonized System (GHS).

- Hazard pictograms



GHS07 GHS08

- **Signal word** Warning

- Hazard-determining components of labeling:

Pigment

- Hazard statements

H315+H320 Causes skin and eye irritation.

H373 May cause damage to organs through prolonged or repeated exposure.

- Precautionary statements

P260 Do not breathe dust/fume/gas/mist/vapors/spray.

P264 Wash thoroughly after handling.

P280 Wear protective gloves.

P302+P352 If on skin: Wash with plenty of water.

P321 Specific treatment (see on this label).

P305+P351+P338 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P314 Get medical advice/attention if you feel unwell.

P332+P313 If skin irritation occurs: Get medical advice/attention.

Safety Data Sheet

acc. to OSHA HCS

Date of issue: 07/23/2026

Reviewed on 07/23/2026

Trade name: ST-3® Thread Sealant

(Contd. of page 1)

P362+P364 Take off contaminated clothing and wash it before reuse.
 P337+P313 If eye irritation persists: Get medical advice/attention.
 P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

- Other hazards

- Results of PBT and vPvB assessment

- **PBT:** Not applicable
- **vPvB:** Not applicable

- Classification according to (d)(1)(ii) of § 1910.1200

The SDS issuer does not object to the classifications provided by importers or manufacturers of precursor products.

- Hazards not otherwise classified

There are no adverse physical or health effects known that are not covered by the hazard classes of the Hazard Communications Standard.

* 3 Composition/information on ingredients

- Chemical characterization: Mixtures

- **Description:** Mixture of the substances listed below with nonhazardous additions.

- Dangerous components:

	Acrylic polymer	10 – 30%
	Skin irritation 2, H315; Specific target organ toxicity (single exposure) 3, H335-H336; Eye irritation 2B, H320	
	Pigment	10 – 30%
	Specific target organ toxicity (repeated exposure) 2, H373	
CAS: 12001-26-2	Mica	7 – 13%
CAS: 13463-67-7	titanium dioxide	5 – 10%
	Acrylic polymer	1 – 5%
	Eye irritation 2B, H320	
CAS: 64742-55-8	Mineral oil, light paraffinic	1 – 5%
	Carcinogenicity 1B, H350	
CAS: 7558-79-4	Di-Sodium Phosphate	1 – 5%
	Skin irritation 2, H315	
CAS: 14808-60-7	Crystalline Silica	0.1 – 1%
	Carcinogenicity 1A, H350; Specific target organ toxicity (repeated exposure) 1, H372	

4 First-aid measures

- Description of first aid measures

- General information:

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

- After inhalation:

In case of unconsciousness place patient stably in side position for transportation.

Supply fresh air; consult doctor in case of complaints.

- After skin contact: Immediately wash with water and soap and rinse thoroughly.

- After eye contact: Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

- After swallowing: Immediately call a doctor.

- Most important symptoms and effects, both acute and delayed

No further relevant information available.

- Indication of any immediate medical attention and special treatment needed

No further relevant information available.

5 Fire-fighting measures

- Extinguishing media

- **Suitable extinguishing agents:** Use fire fighting measures that suit the environment.

- Special hazards arising from the substance or mixture

No further relevant information available.

- Advice for firefighters

- Protective equipment:

Wear self-contained respiratory protective device.

Wear fully protective suit.

6 Accidental release measures

- Personal precautions, protective equipment and emergency procedures

Ensure adequate ventilation

Wear protective clothing.

- Environmental precautions:

Inform respective authorities in case of seepage into water course or sewage system.

Do not allow to enter sewers/ surface or ground water.

- Methods and material for containment and cleaning up:

Dispose contaminated material as waste according to section 13.

(Contd. on page 3)

Safety Data Sheet

acc. to OSHA HCS

Date of issue: 07/23/2026

Reviewed on 07/23/2026

Trade name: ST-3® Thread Sealant

(Contd. of page 2)

Ensure adequate ventilation.
Dispose of the collected material according to regulations.

- Reference to other sections

See Section 7 for information on safe handling.
See Section 8 for information on personal protection equipment.
See Section 13 for disposal information.

7 Handling and storage

- Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace.
Open and handle receptacle with care.

- **Information about protection against explosions and fires:** Keep respiratory protective device available.

- Conditions for safe storage, including any incompatibilities

- Storage:

- **Requirements to be met by storerooms and receptacles:** No special requirements.

- **Information about storage in one common storage facility:** Not required

- **Further information about storage conditions:**

Keep receptacle tightly sealed.

Store in cool, dry conditions in well sealed receptacles.

- **Specific end use(s)** No further relevant information available.

8 Exposure controls/personal protection

- Control parameters

- **Components with limit values that require monitoring at the workplace:**

At this time, the other constituents have no known exposure limits.

CAS: 12001-26-2 Mica

PEL Long-term value: 20 mppcf ppm
<1% crystalline silica

REL Long-term value: 3* mg/m³
*respirable dust; containing < 1% quartz

TLV Long-term value: 0.1 mg/m³
*Respirable particulate matter

CAS: 13463-67-7 titanium dioxide

PEL Long-term value: 15* mg/m³
*total dust

REL See Pocket Guide App. A

TLV Long-term value: 0.2* 2.5** mg/m³
resp. fraction, *nanoscale, **finescale, A3

CAS: 14808-60-7 Crystalline Silica

PEL Long-term value: 0.05* mg/m³
*resp. dust; 30mg/m³/%SiO₂+2

REL Long-term value: 0.05* mg/m³
*respirable dust; See Pocket Guide App. A

TLV Long-term value: 0.025* mg/m³
*respirable particulate matter, A2

- **Additional information:** The lists that were valid during the creation were used as basis.

- Exposure controls

- **Appropriate engineering controls** No further data; see section 7.

- Personal protective equipment:

- General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.
Immediately remove all soiled and contaminated clothing.
Wash hands before breaks and at the end of work.
Store protective clothing separately.
Avoid contact with the eyes and skin.

- Breathing equipment:

Not required

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.

- Protection of hands:



Protective gloves

(Contd. on page 4)

Safety Data Sheet

acc. to OSHA HCS

Date of issue: 07/23/2026

Reviewed on 07/23/2026

Trade name: ST-3® Thread Sealant

(Contd. of page 3)

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

- Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

Nitrile rubber, NBR

- Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

- **Eye protection:** Required use of safety glasses

- **Body protection:** Protective work clothing

* 9 Physical and chemical properties

- Information on basic physical and chemical properties

- General Information

- Physical state

Solid

- Color:

White

- Odor:

Characteristic

- Odor threshold:

Not determined

- Melting point/Melting range:

Undetermined

- Boiling point/Boiling range:

≥ 100 °C (≥ 212 °F)

- Flammability:

Not determined

- Explosion limits:

- Lower:

Not determined

- Upper:

Not determined

- Flash point:

150 °C (302 °F)

- Decomposition temperature:

Not determined

- pH-value:

Not applicable

- Viscosity:

- Kinematic:

Not applicable

- Dynamic at 20 °C (68 °F):

900 mPas

- Solubility in / Miscibility with

- Water:

Insoluble.

- Partition coefficient (n-octanol/water):

Not determined

- Vapor pressure at 20 °C (68 °F):

≤ 23.4 hPa (≤ 17.6 mm Hg)

- Vapor pressure:

- Density at 20 °C (68 °F):

~ 1.89859 g/cm³ (~ 15.84373 lbs/gal)

- Relative density

Not determined

- Vapor density

Not applicable

- Particle characteristics

Not determined

- Other information

- Appearance:

- Form:

Solidified mass

- Important information on protection of health and environment, and on safety.

- Ignition temperature:

Product is not selfigniting.

- Danger of explosion:

Product does not present an explosion hazard.

- Solvent content:

- Water:

0.1 %

- VOC content:

0.00 %

- Solids content:

50.3 %

- Change in condition

- Evaporation rate

Not applicable.

10 Stability and reactivity

- **Reactivity** No further relevant information available.

- Chemical stability

- **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.

- **Possibility of hazardous reactions** No dangerous reactions known.

- **Conditions to avoid** No further relevant information available.

- **Incompatible materials:** No further relevant information available.

- **Hazardous decomposition products:** No dangerous decomposition products known.

(Contd. on page 5)

Safety Data Sheet

acc. to OSHA HCS

Date of issue: 07/23/2026

Reviewed on 07/23/2026

Trade name: ST-3® Thread Sealant

(Contd. of page 4)

*11 Toxicological information

- Information on toxicological effects

- Acute toxicity:

- LD/LC50 values that are relevant for classification:

Acrylic polymer

Oral	LD50	> 5,000 mg/kg (rat)
Dermal	LD50	> 5,000 mg/kg (rabbit)

Pigment

Oral	LD50	5,000 mg/kg (rat)
------	------	-------------------

CAS: 13463-67-7 titanium dioxide

Oral	LD50	> 20,000 mg/kg (rat)
Dermal	LD50	> 10,000 mg/kg (rabbit)
Inhalative	LC50/4 h	> 6.82 mg/l (rat)

Acrylic polymer

Oral	LD50	> 5,000 mg/kg (rat)
Dermal	LD50	> 5,000 mg/kg (rabbit)

CAS: 7558-79-4 Di-Sodium Phosphate

Oral	LD50	17,000 mg/kg (rat)
------	------	--------------------

- Primary irritant effect:

- **on the skin:** Irritant to skin and mucous membranes.

- **on the eye:** Irritating effect.

- **Sensitization:** No sensitizing effects known.

- Additional toxicological information:

The product shows the following dangers according to internally approved calculation methods for preparations:

Harmful

Irritant

Carcinogenic.

- **Interactive effects** No interactive effects between components are known.

- Carcinogenic categories

- IARC (International Agency for Research on Cancer)

CAS: 13463-67-7	titanium dioxide	2B
CAS: 9002-84-0	Polytetrafluoroethylene	3
CAS: 7631-86-9	Silicon dioxide, Untreated fumed	3
CAS: 14808-60-7	Crystalline Silica	1

- NTP (National Toxicology Program)

CAS: 14808-60-7	Crystalline Silica	K
-----------------	--------------------	---

- OSHA-Ca (Occupational Safety & Health Administration)

None of the ingredients is listed.

- **Alternative sources for toxicological information** No non-standard sources for toxicological information where used.

12 Ecological information

- Toxicity

- **Aquatic toxicity:** No further relevant information available.

- **Persistence and degradability** No further relevant information available.

- **Bioaccumulative potential** No further relevant information available.

- **Mobility in soil** No further relevant information available.

- Results of PBT and vPvB assessment

- **PBT:** Not applicable

- **vPvB:** Not applicable

- Other adverse effects

- **Remark:** Harmful to fish

- Additional ecological information:

- General notes:

Water hazard class 3 (Self-assessment): extremely hazardous for water

Do not allow product to reach ground water, water course or sewage system, even in small quantities.

Danger to drinking water if even extremely small quantities leak into the ground.

Harmful to aquatic organisms

(Contd. on page 6)

Safety Data Sheet

acc. to OSHA HCS

Date of issue: 07/23/2026

Reviewed on 07/23/2026

Trade name: ST-3® Thread Sealant

(Contd. of page 5)

13 Disposal considerations

- Waste treatment methods

- **Recommendation:** Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

- Uncleaned packagings:

- **Recommendation:** Disposal must be made according to official regulations.

14 Transport information

- UN-Number	
- DOT, ADN, IMDG, IATA	not regulated
- UN proper shipping name	
- DOT, ADN, IMDG, IATA	not regulated
- Transport hazard class(es)	
- DOT, ADN, IMDG, IATA	
- Class	not regulated
- Packing group	
- DOT, IMDG, IATA	not regulated
- Environmental hazards:	
- Marine pollutant:	No
- Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code	Not applicable
- Special precautions for user	Not applicable
- UN "Model Regulation":	not regulated

15 Regulatory information

- Safety, health and environmental regulations/legislation specific for the substance or mixture

- Sara

- Section 355 (extremely hazardous substances):

None of the ingredients is listed.

- Section 313 (Specific toxic chemical listings):

CAS: 3251-23-8 | copper dinitrate

- TSCA (Toxic Substances Control Act):

All components have the value ACTIVE.

- Hazardous Air Pollutants

None of the ingredients is listed.

- Proposition 65

- Chemicals known to cause cancer:

	Acrylic polymer
	Pigment
CAS: 14808-60-7	Crystalline Silica

- Chemicals known to cause reproductive toxicity for females:

None of the ingredients is listed.

- Chemicals known to cause reproductive toxicity for males:

None of the ingredients is listed.

- Chemicals known to cause developmental toxicity:

Acrylic polymer

- Carcinogenic categories

- EPA (Environmental Protection Agency)

None of the ingredients is listed.

- TLV (Threshold Limit Value)

CAS: 13463-67-7	titanium dioxide	A4
CAS: 1332-58-7	Kaolin	A4
CAS: 14808-60-7	Crystalline Silica	A2

(Contd. on page 7)

Safety Data Sheet

acc. to OSHA HCS

Date of issue: 07/23/2026

Reviewed on 07/23/2026

Trade name: ST-3® Thread Sealant

(Contd. of page 6)

- NIOSH-Ca (National Institute for Occupational Safety and Health)	
CAS: 13463-67-7	titanium dioxide
CAS: 14808-60-7	Crystalline Silica

- National regulations:

- Information about limitation of use:

Workers are not allowed to be exposed to the hazardous carcinogenic materials contained in this preparation. Exceptions can be made by the authorities in certain cases.

- **Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- **Department issuing SDS:** H.B. Fuller Company | ND Industries Health and Environmental Affairs

- **Contact:** Safety, Health and Environmental Affairs

- Classification System:

- HMIS-ratings (scale 0 - 4)

HEALTH	1	Health = *1
FIRE	1	Fire = 1
REACTIVITY	0	Reactivity = 0

- NFPA ratings (scale 0 - 4)

1	1	0
Health = 1	Fire = 1	Reactivity = 0

- **Date of previous version** 02/24/2025

- **Version number of previous version:** 39

- **Date of preparation** 07/23/2026

- Abbreviations and acronyms:

IMDG: International Maritime Code for Dangerous Goods
 DOT: US Department of Transportation
 IATA: International Air Transport Association
 EINECS: European Inventory of Existing Commercial Chemical Substances
 ELINCS: European List of Notified Chemical Substances
 CAS: Chemical Abstracts Service (division of the American Chemical Society)
 VOC: Volatile Organic Compounds (USA, EU)
 LC50: Lethal concentration, 50 percent
 LD50: Lethal dose, 50 percent
 PBT: Persistent, Bioaccumulative and Toxic
 vPvB: very Persistent and very Bioaccumulative
 NIOSH: National Institute for Occupational Safety
 OSHA: Occupational Safety & Health
 TLV: Threshold Limit Value
 PEL: Permissible Exposure Limit
 REL: Recommended Exposure Limit
 Skin irritation 2: Skin corrosion/irritation – Category 2
 Eye irritation 2B: Serious eye damage/eye irritation – Category 2B
 Carcinogenicity 1A: Carcinogenicity – Category 1A
 Carcinogenicity 1B: Carcinogenicity – Category 1B
 Specific target organ toxicity (single exposure) 3: Specific target organ toxicity (single exposure) – Category 3
 Specific target organ toxicity (repeated exposure) 1: Specific target organ toxicity (repeated exposure) – Category 1
 Specific target organ toxicity (repeated exposure) 2: Specific target organ toxicity (repeated exposure) – Category 2

- * **Data compared to the previous version altered.**

- Disclaimer

IMPORTANT: Information, specifications, procedures and recommendations provided ("information") are based on our experience and we believe this to be accurate. No representation, guarantee or warranty is made as to the accuracy or completeness of the information, or that use of the product will avoid losses or damages or give desired results. It is user's sole responsibility to test and determine the suitability of any product for the intended use. Tests should be repeated if materials or conditions change in any way. The user is advised to review the specific context of the intended use to determine whether the user's intended use violates any law or infringes upon any patent(s). No employee, distributor or agent has any right to change these facts and offer a guarantee of performance.

H.B. Fuller, ND, ND Industries, and Vibra-TITE are registered trademarks of the H. B. Fuller Company.