

涂料、油漆、润滑剂

特种涂料包括油漆，润滑剂，和客制，可用于很多方面的高效能的表面处理，包括汽车总成如弹簧，窗户轨道，座位滑轨，支架，弹簧夹和铰链。



特种涂料是广泛的产品通常旨在提供干的油膜润滑和表现特性于各种工业和汽车应用。

应用:

减少安装扭矩的工具，金属表面保护，弹簧、弹簧夹、垫片

特点:

ND完整的涂料产品提供一个或多个以下几功能:

- 润滑
- 温度保护
- 减少摩擦/改善
- 耐蚀性
- 扭矩张力改善
- 夹紧负载和改善
- 预防卡死
- 预防堵塞和堆积
- 增强美观和识别

处理: 专业涂料可以透过浸泡甩干，浸泡滴干、浇淋或喷涂来加工。

水基功能: 大多数供应商只提供溶剂。

不同配方: 特种涂料配方有环氧、丙烯酸和聚氨酯基的涂料，ND可提供水基型及溶剂型。

涂料附着: 特殊涂料可附着于不同的材料上。

环保: 水基型配方可有较低的挥发性的有机化合物。

长寿命: 部件上的特殊涂料是无寿命限制，储存条件(+ 40 ° F(+ 4 ° C)+ 90 ° F(+ 32 ° C))，但是一年须认证一次。



规格满足:

AUTOMOTIVE:

特定的专业涂料配方满足或超过以下规格的性能要求:

- Chrysler: PS-7001
- Ford: ESE-M13P6-B1, ESE-M13P6-B2, ESF-M13P6-A, WSS-M21P28-A2, WSS-M21P33-A

COMPETES WITH:

- Emralon® 305, 330, 333,334, 338, & GP 1904, Moly Dag® 210
- Teflon-S® 954-100 Series & 954-H62459
- Xylan® 5251® /840, 1661, 1010
- Macugard™ #17130 & UV Fluid #19932
- Formkote® HL
- Moly cote®

SPECIFICATIONS:

Identifier	Resin System	Description
SC502HV (#006)	Polyurethane	Torque tension modifying; Paintable; Dry, firm lubricant
SC503 (SC13-06)	Wax	Non-crosslinked wax emulsion coating with extremely low coefficient of friction. Contains fluorescent tracer.
SC603 (SC10-07)	Polyurethane	Chemical resistant and corrosion resistant coating with extremely low coefficient of friction
SC604	Acrylic	Dry film lubricant for fasteners. Reduces installation torque and helps prevent galling and seizing.

Emralon and Moly Dag are registered trademarks of Acheson Industries, Inc. Teflon is a registered trademark of E.I. DuPont de Nemours & Company Inc. Xylan is a registered trademark of Whitford Corporation. Macugard is a trademark of Mac Dermid Inc. Formkote is a registered trademark of E/M Corporation. Moly Cote is a registered trademark of Dow Corning Company.

ND Industries is a registered trademark of ND Industries, Inc.



稳得电子(昆山)有限公司
ND Electronics (Kunshan) Co., Ltd.

中国江苏省昆山市城北区玉城中路395号 邮编: 215300 电话: 86-512-5776-5335 传真: 86-512-5775-5353
Web Site: www.ndindustries.com • E-mail: ndchina@ndindustries.com