



Safety Data Sheet acc. to OSHA HCS

Printing date 07/13/2015

Reviewed on 06/03/2015

1 Identification

- Product identifier

- Trade name: ND Microspheres® Acrylic Series

- Synonyms: AA1196
- Part number: AA1196

- Relevant identified uses of the substance or mixture Thread locker

- Details of the supplier of the safety data sheet

- Manufacturer/Supplier: ND Industries, Inc 1000 North Crooks Road Clawson, MI 48017 USA Telephone: +1-248-288-0000 Email: info@ndindustries.com Website: www.ndindustries.com

- Information department: Product safety department

- Emergency telephone number: United States: 1-800-424-9300 International: +1-703-527-3887

2 Hazard(s) identification

Classification of the substance or mixture



Skin Irrit. 2 H315 Causes skin irritation.

Skin Sens. 1 H317 May cause an allergic skin reaction.

Eye Irrit. 2B H320 Causes eye irritation.

Label elements

- GHS label elements The product is classified and labeled according to the Globally Harmonized System (GHS). Hazard pictograms



- Signal word Warning

- Hazard-determining components of labeling:
- Ethoxylated dimethacrylate
- Hazard statements
- H315+H320 Causes skin and eye irritation.
- H317 May cause an allergic skin reaction.

Precautionary statements

- Avoid breathing dust/fume/gas/mist/vapors/spray P261
- P280 Wear protective gloves.
- P264 Wash thoroughly after handling. P272
 - Contaminated work clothing must not be allowed out of the workplace.

P305+P351+P338 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

- P363 Wash contaminated clothing before reuse.
- P333+P313 If skin irritation or rash occurs: Get medical advice/attention. If eye irritation persists: Get medical advice/attention.
- P337+P313
- P302+P352 If on skin: Wash with plenty of water. P321
- Specific treatment (see on this label).
- P362+P364 Take off contaminated clothing and wash it before reuse.
- P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

(Contd. on page 2)

Trade name: ND Microspheres® Acrylic Series

(Contd. of page 1)

Reviewed on 06/03/2015

Classification system: NFPA ratings (scale 0 - 4)



- HMIS-ratings (scale 0 - 4)



- Other hazards

Results of PBT and vPvB assessment

- PBT: Not applicable.
- vPvB: Not applicable.

3 Composition/information on ingredients

- Chemical characterization: Mixtures

- Description: Mixture of the substances listed below with nonhazardous additions.

- Dangerous components:

Ethoxylated dimethacrylate	20-30%
Intermediate copolymer	1-5%
4 First-aid measures	

- Description of first aid measures

- After inhalation:

Supply fresh air and to be sure call for a doctor.

- In case of unconsciousness place patient stably in side position for transportation.
- Supply fresh air; consult doctor in case of complaints.
- After skin contact: Immediately wash with water and soap and rinse thoroughly.
- After eye contact: Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.
- After swallowing: If symptoms persist consult doctor.
- Information for doctor:
 - Most important symptoms and effects, both acute and delayed No further relevant information available.
 - Indication of any immediate medical attention and special treatment needed
 - No further relevant information available.

5 Fire-fighting measures

Extinguishing media

Suitable extinguishing agents:

CO2, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

Use fire fighting measures that suit the environment.

- Special hazards arising from the substance or mixture No further relevant information available.

- Advice for firefighters

- Protective equipment:

Wear self-contained respiratory protective device. Wear fully protective suit.

6 Accidental release measures

- Personal precautions, protective equipment and emergency procedures

Ensure adequate ventilation

Wear protective clothing.

- Environmental precautions: Do not allow to enter sewers/ surface or ground water.

- Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust). Ensure adequate ventilation.

Dispose of the collected material according to regulations.

- Reference to other sections
- See Section 7 for information on safe handling.
- See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

Trade name: ND Microspheres® Acrylic Series

(Contd. of page 2)

Reviewed on 06/03/2015

7 Handling and storage

- Handling:

- Precautions for safe handling
- Ensure good ventilation/exhaustion at the workplace.
- Prevent formation of aerosols.
- No special precautions are necessary if used correctly.

- Information about protection against explosions and fires: No special measures required.

- Conditions for safe storage, including any incompatibilities

- Storage:

- Requirements to be met by storerooms and receptacles: No special requirements.
- Information about storage in one common storage facility: Not required.
- Further information about storage conditions: Keep receptacle tightly sealed.
- Store in each dry conditions in well a

Store in cool, dry conditions in well sealed receptacles. - Specific end use(s) No further relevant information available.

8 Exposure controls/personal protection

- Additional information about design of technical systems: No further data; see item 7.

- Control parameters

Components with limit values that require monitoring at the workplace:

The product does not contain any relevant quantities of materials with critical values that have to be monitored at the workplace. - Additional information: The lists that were valid during the creation were used as basis.

- Exposure controls

- Personal protective equipment:

General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing.

Wash hands before breaks and at the end of work.

Avoid contact with the eyes and skin.

- Breathing equipment:

Not required.

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.

- Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

- Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

- Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

- Eye protection:



Tightly sealed goggles

Body protection: Protective work clothing

9 Physical and chemical properties

- Information on basic physical and chemical properties - General Information - Appearance:		
- Form:	Fluid	
- Color:	Light blue	
- Odor:	Characteristic	
 Odour threshold: 	Not determined.	

Trade name: ND Microspheres® Acrylic Series

Reviewed on 06/03/2015

- Privature. Not determined. - Change in condition - Melting point/Melting range: Undetermined. - Boiling point/Boiling range: 100 °C (212 °F) - Flash point: 101 °C (214 °F) - Flammability (solid, gaseous): Not applicable. - Ignition temperature: - - Decomposition temperature: Not determined. - Auto igniting: Product is not selfigniting. - Danger of explosion: Product does not present an explosion hazard. - Explosion limits: - - Lower: Not determined. - Vapor pressure at 20 °C (68 °F): 23 hPa (17 mm Hg) - Density at 20 °C (68 °F): 1.05 g/cm³ (8.762 lbs/gal) - Relative density Not determined. - Vapour density Not determined. - Solubility in / Miscibility with Not determined. - Viscosity: Not determined. - Viscosity: Not determined. - Solubility in / Miscibility with Not determined. - Viscosity: Not determined. - Viscosity: 1500 mPas - Kinematic: Not determined. - Solvent content: 0.3 %		(Contd. o
· Melting point/Melting range: Undetermined. · Boiling point/Boiling range: 100 °C (212 °F) · Flash point: 101 °C (214 °F) · Flammability (solid, gaseous): Not applicable. · Ignition temperature: Not determined. · Decomposition temperature: Not determined. · Decomposition temperature: Product is not selfigniting. · Danger of explosion: Product does not present an explosion hazard. · Explosion limits: - Lower: · Lower: Not determined. · Upper: Not determined. · Upper: Not determined. · Vapor pressure at 20 °C (68 °F): 23 hPa (17 mm Hg) · Relative density Not determined. · Vapour density Not determined. · Vater: Not determined. · Solubility in / Miscibility with Not determined. · Viscosity: - Solubility in / An miscibile or difficult to mix. · Partition coefficient (n-octanol/water): Not determined. - Organic solvents: · Organic	- pH-value:	Not determined.
Boiling point/Boiling range: 100 °C (212 °F) Flash point: 101 °C (214 °F) Flammability (solid, gaseous): Not applicable. Ignition temperature: Not determined. - Decomposition temperature: Not determined. - Auto igniting: Product is not selfigniting. Danger of explosion: Product does not present an explosion hazard. Explosion limits: - Lower: - Lower: Not determined. - Upper: Not determined. - Vapor pressure at 20 °C (68 °F): 23 hPa (17 mm Hg) Density at 20 °C (68 °F): 1.05 g/cm³ (8.762 lbs/gal) - Relative density Not determined. - Vapor pressure at 20 °C (68 °F): 1.05 g/cm³ (8.762 lbs/gal) - Relative density Not determined. - Vapour density Not determined.		Undetermined
- Flash point: 101 °C (214 °F) - Flammability (solid, gaseous): Not applicable. - Ignition temperature: Not determined. - Decomposition temperature: Not determined. - Auto igniting: Product is not selfigniting. - Danger of explosion: Product does not present an explosion hazard. - Explosion limits: - - Lower: Not determined. - Upper: Not determined. - Vapor pressure at 20 °C (68 °F): 23 hPa (17 mm Hg) - Density at 20 °C (68 °F): 1.05 g/cm³ (8.762 lbs/gal) - Relative density Not determined. - Vapour density Not determined. - Vapour density Not determined. - Solubility in / Miscibility with - - Water: Not determined. - Solubility in / Miscibility with - - Water: Not determined. - Viscosity: - - Dynamic at 20 °C (68 °F): 1500 mPas - Kinematic: Not determined. - Organic solvents: 0.3 % - Water: S9.2 % - VOC content: 0.3 % - Organic		
Flammability (solid, gaseous): Not applicable. Ignition temperature: Not determined. - Decomposition temperature: Not determined. - Auto igniting: Product is not selfigniting. Danger of explosion: Product does not present an explosion hazard. Explosion limits: - - Lower: Not determined. - Upper: Not determined. - Vapor pressure at 20 °C (68 °F): 23 hPa (17 mm Hg) Density at 20 °C (68 °F): 1.05 g/cm³ (8.762 lbs/gal) - Relative density Not determined. - Vapour density Not determined. - Evaporation rate Not determined. - Solubility in / Miscibility with Not determined. - Evaporation rate Not determined. - Solubility in / Miscibility with Not determined. - Viscosity: - - Dynamic at 20 °C (68 °F): 1500 mPas - Kinematic: Not determined. Solvent content: - - Organic solvents: 0.3 % - Water: S3.2 % - VOC content: 0.3 % - Solids content: 40.4 %		
Ignition temperature: Not determined. • Decomposition temperature: Not determined. • Auto igniting: Product is not selfigniting. • Danger of explosion: Product does not present an explosion hazard. • Explosion limits: - • Lower: Not determined. • Upper: Not determined. • Vapor pressure at 20 °C (68 °F): 23 hPa (17 mm Hg) • Density at 20 °C (68 °F): 1.05 g/cm³ (8.762 lbs/gal) • Relative density Not determined. • Vapour density Not determined. • Solubility in / Miscibility with Not miscible or difficult to mix. • Partition coefficient (n-octanol/water): Not determined. • Viscosity: 1500 mPas • Kinematic: Not determined. • Organic solvents: 0.3 % • Water: 59.2 % • VOC content: 0.3 % • Solids content:	-	
· Decomposition temperature: Not determined. · Auto igniting: Product is not selfigniting. · Danger of explosion: Product does not present an explosion hazard. · Explosion limits: - · Lower: Not determined. · Upper: Not determined. · Vapor pressure at 20 °C (68 °F): 23 hPa (17 mm Hg) · Density at 20 °C (68 °F): 1.05 g/cm³ (8.762 lbs/gal) · Relative density Not determined. · Vapour density with Not miscible or difficult to mix. · Partition coefficient (n-octanol/water): Not determined. · Viscosity: Dynamic at 20 °C (68 °F): 1500 mPas · Kinematic: Not determined. · Solvent content: 0.3 % Not determined. · VOC content: 0.3 % 3.3 g/l / 0.03 lb/gl · VOC content: 0.3 % 3.3 g/l / 0.03 lb/gl <td></td> <td>Not applicable.</td>		Not applicable.
Auto igniting: Product is not selfigniting. Danger of explosion: Product does not present an explosion hazard. Explosion limits: - - Lower: Not determined. - Upper: Not determined. - Vapor pressure at 20 °C (68 °F): 23 hPa (17 mm Hg) - Density at 20 °C (68 °F): 1.05 g/cm³ (8.762 lbs/gal) - Relative density Not determined. - Vapour density with Not determined. - Vapour density in / Miscibility with Not miscible or difficult to mix. - Partition coefficient (n-octanol/water): Not determined. - Viscosity: Dynamic at 20 °C (68 °F): 1500 mPas - Kinematic: Not determined. - Solvent content: 0.3 % - Organic solvents: 0.3 % - Water: 59.2 % - VOC content: 3.3 g/l / 0.03 lb/gl - Solids content: 40.4 %	- Ignition temperature:	
• Danger of explosion: Product does not present an explosion hazard. • Explosion limits: - • Lower: Not determined. • Upper: Not determined. • Vapor pressure at 20 °C (68 °F): 23 hPa (17 mm Hg) • Density at 20 °C (68 °F): 1.05 g/cm³ (8.762 lbs/gal) • Relative density Not determined. • Vapour density Not determined. • Vater: Not determined. • Viscosity: Not determined. • Viscosity: 1500 mPas • Kinematic: Not determined. • Organic solvents: 0.3 % • Water: 59.2 % • VOC content: 0.3 % 3.3 g/l / 0.03 lb/gl 3.3 g/l / 0.03 lb/gl	 Decomposition temperature: 	Not determined.
• Explosion limits: Not determined. • Lower: Not determined. • Upper: Not determined. • Vapor pressure at 20 °C (68 °F): 23 hPa (17 mm Hg) • Density at 20 °C (68 °F): 1.05 g/cm³ (8.762 lbs/gal) • Relative density Not determined. • Vapour density Not determined. • Viscosity: Not miscible or difficult to mix. • Partition coefficient (n-octanol/water): Not determined. Viscosity: • Dynamic at 20 °C (68 °F): 1500 mPas • Kinematic: Not determined. • Solvent content: 0.3 % • Water: 59.2 % • VOC content: 0.3 % 3.3 g/l / 0.03 lb/gl 3.3 g/l / 0.03 lb/gl	- Auto igniting:	Product is not selfigniting.
· Lower: Not determined. · Upper: Not determined. · Vapor pressure at 20 °C (68 °F): 23 hPa (17 mm Hg) · Density at 20 °C (68 °F): 1.05 g/cm³ (8.762 lbs/gal) · Relative density Not determined. · Vapour density in / Miscibility with Not determined. · Water: Not miscible or difficult to mix. · Partition coefficient (n-octanol/water): Not determined. · Viscosity: 1500 mPas · Kinematic: Not determined. · Organic at 20 °C (68 °F): 1500 mPas · Kinematic: Not determined. · Voc content: 0.3 % · Water: 59.2 % · VOC content: 0.3 % · Water: 59.2 % · VOC content: 0.3 % · Solids content: 40.4 %	- Danger of explosion:	Product does not present an explosion hazard.
· Upper: Not determined. · Vapor pressure at 20 °C (68 °F): 23 hPa (17 mm Hg) · Density at 20 °C (68 °F): 1.05 g/cm³ (8.762 lbs/gal) · Relative density Not determined. · Vapour density with Not determined. · Solubility in / Miscibility with Not determined. · Water: Not determined. · Viscosity: 1500 mPas · Kinematic: Not determined. · Solvent content: 0.3 % · Water: 59.2 % · VOC content: 0.3 % · VOC content: 0.3 % · Solids content: 40.4 %	- Explosion limits:	
 Vapor pressure at 20 °C (68 °F): 23 hPa (17 mm Hg) Density at 20 °C (68 °F): 1.05 g/cm³ (8.762 lbs/gal) Relative density Not determined. Vapour density Not determined. Evaporation rate Not determined. Solubility in / Miscibility with Water: Not miscible or difficult to mix. Partition coefficient (n-octanol/water): Not determined. Viscosity: Dynamic at 20 °C (68 °F): 1500 mPas Kinematic: Not determined. Solvent content: Organic solvents: 0.3 % Water: Sol.3 g/l / 0.03 lb/gl Solids content: 40.4 % 		Not determined.
- Density at 20 °C (68 °F): 1.05 g/cm³ (8.762 lbs/gal) - Relative density Not determined. - Vapour density Not determined. - Evaporation rate Not determined. - Solubility in / Miscibility with Not miscible or difficult to mix. - Partition coefficient (n-octanol/water): Not determined. - - Viscosity: - - Dynamic at 20 °C (68 °F): 1500 mPas - Kinematic: Not determined. - Solvent content: - - Organic solvents: 0.3 % - Water: 59.2 % - VOC content: 0.3 % - Solids content: 40.4 %	- Upper:	Not determined.
- Relative density Not determined. - Vapour density Not determined. - Evaporation rate Not determined. - Solubility in / Miscibility with Not miscible or difficult to mix. - Vater: Not miscible or difficult to mix. - Partition coefficient (n-octanol/water): Not determined. - - Viscosity: - - Dynamic at 20 °C (68 °F): 1500 mPas - Kinematic: Not determined. - Solvent content: - - Organic solvents: 0.3 % - Water: 59.2 % - VOC content: 0.3 % - Solids content: 40.4 %	- Vapor pressure at 20 °C (68 °F):	23 hPa (17 mm Hg)
· Vapour densityNot determined.· Evaporation rateNot determined.· Solubility in / Miscibility with · Water:Not miscible or difficult to mix.· Partition coefficient (n-octanol/water): Not determined.Not miscible or difficult to mix.· Viscosity: · Dynamic at 20 °C (68 °F):1500 mPas Not determined.· Viscosity: 		1.05 g/cm³ (8.762 lbs/gal)
- Evaporation rate Not determined. - Solubility in / Miscibility with - Water: Not miscible or difficult to mix. - Partition coefficient (n-octanol/water): Not determined. - - Viscosity: - Dynamic at 20 °C (68 °F): 1500 mPas Not determined. - Kinematic: Not determined. - Solvent content: - Organic solvents: 0.3 % 0.3 % 0.3 % 0.3 % 0.3 % - VOC content: 0.3 % 0.3 % 0.3 % - Solids content: 40.4 %		Not determined.
Solubility in / Miscibility with - Water: Not miscible or difficult to mix. Partition coefficient (n-octanol/water): Not determined. Viscosity: - Dynamic at 20 °C (68 °F): 1500 mPas - Kinematic: Not determined. Solvent content: - Organic solvents: 0.3 % - Water: 59.2 % - VOC content: 0.3 % - Solids content: 40.4 %		Not determined.
- Water: Not miscible or difficult to mix. - Partition coefficient (n-octanol/water): Not determined. - Viscosity: - Dynamic at 20 °C (68 °F): 1500 mPas - Kinematic: Not determined. - Solvent content: - Organic solvents: 0.3 % - Water: 59.2 % - VOC content: 0.3 % - VOC content: 0.4 %	 Evaporation rate 	Not determined.
- Partition coefficient (n-octanol/water): Not determined. - Viscosity: - Dynamic at 20 °C (68 °F): 1500 mPas - Kinematic: Not determined. - Solvent content: 0.3 % - Water: 59.2 % - VOC content: 0.3 % - VOC content: 0.3 % - Solids content: 40.4 %		
- Viscosity: - Dynamic at 20 °C (68 °F): 1500 mPas - Kinematic: Not determined. - Solvent content: 0.3 % - Water: 59.2 % - VOC content: 0.3 % - VOC content: 0.3 % - Solids content: 40.4 %	- Water:	Not miscible or difficult to mix.
- Dynamic at 20 °C (68 °F): 1500 mPas - Kinematic: Not determined. - Organic solvents: 0.3 % - Water: 59.2 % - VOC content: 0.3 % - Solids content: 40.4 %	- Partition coefficient (n-octanol/wa	ater): Not determined.
· Kinematic: Not determined. · Solvent content: 0.3 % · Organic solvents: 0.3 % · Water: 59.2 % · VOC content: 0.3 % 3.3 g/l / 0.03 lb/gl - Solids content: 40.4 %		
- Solvent content: 0.3 % - Organic solvents: 0.3 % - Water: 59.2 % - VOC content: 0.3 % 3.3 g/l / 0.03 lb/gl - Solids content: 40.4 %		1500 mPas
- Organic solvents: 0.3 % - Water: 59.2 % - VOC content: 0.3 % 3.3 g/l / 0.03 lb/gl 3.3 g/l / 0.03 lb/gl	- Kinematic:	Not determined.
- Water: 59.2 % - VOC content: 0.3 % 3.3 g/l / 0.03 lb/gl - Solids content: 40.4 %	- Solvent content:	
- VOC content: 0.3 % 3.3 g/l / 0.03 lb/gl - Solids content: 40.4 %		0.3 %
3.3 g/l / 0.03 lb/gl - Solids content: 40.4 %		
- Solids content: 40.4 %	 VOC content: 	
		3.3 g/l / 0.03 lb/gl
Other information No further relevant information available.		40.4 %
	Other information	No further relevant information available.

- Reactivity

- Chemical stability

- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.

- Possibility of hazardous reactions No dangerous reactions known.

- **Conditions to avoid** No further relevant information available.

- Incompatible materials: No further relevant information available.

- Hazardous decomposition products:

Aldehyde

Hydrocarbons

11 Toxicological information

Information on toxicological effects

- Acute toxicity:

- LD/LC50 values that are relevant for classification:

Intermediate copolymer

Oral LD50 >5000 mg/kg (rat)

Primary irritant effect:

- on the skin: Irritant to skin and mucous membranes.

- on the eye: Irritating effect.

- Sensitization: Sensitization possible through skin contact.

- Additional toxicological information:

The product shows the following dangers according to internally approved calculation methods for preparations:

Reviewed on 06/03/20
(Contd. of page
(************
ourse or sewage system.
o not allow product to reach sewage system.
·····

 Packing group
 DOT, IMDG, IATA not regulated - Environmental hazards: - Marine pollutant: No - Special precautions for user Not applicable. - Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code Not applicable. - UN "Model Regulation": -

15 Regulatory information

- Safety, health and environmental regulations/legislation specific for the substance or mixture - Sara

	- Section 355 (extremely hazardous substances):		
None	None of the ingredients is listed.		
	- Section 313 (Specific toxic chemical listings):		
None of	of the ingredients is listed.		

Trade name: ND Microspheres® Acrylic Series

Reviewed on 06/03/2015

	(Contd. of pag
- TSCA (Toxic Substa	nces Control Act):
Octanol	
N,N-Diethyl-P-Toluidine	
N,N-dimethyl-o-toluidine	
Deionized water	
 Proposition 65 	
	n to cause cancer:
None of the ingredients is listed.	
- Chemicals know	n to cause reproductive toxicity for females:
None of the ingredients is listed.	
- Chemicals know	n to cause reproductive toxicity for males:
None of the ingredients is listed.	
- Chemicals know	n to cause developmental toxicity:
None of the ingredients is listed.	
- Carcinogenic catego	
	ntes ntal Protection Agency)
None of the ingredients is listed.	nial Protection Agency)
8	
•	Limit Value established by ACGIH)
None of the ingredients is listed.	
	nal Institute for Occupational Safety and Health)
None of the ingredients is listed.	
Chemical safety assessme	nt: A Chemical Safety Assessment has not been carried out.
Other information	
This information is based on our shall not establish a legally valid	present knowledge. However, this shall not constitute a guarantee for any specific product features and contractual relationship.
Department issuing SDS: N	ID Industries, Inc Safety, Health and Environmental Affaires
Contact: Safety, Health and Er	
- Date of preparation / las	
IMDG: International Maritime Code for DOT: US Department of Transportatic IATA: International Air Transport Assc ACGIH: American Conference of Gow EINECS: European Inventory of Existi ELINCS: European List of Notified Ch	rt des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road) r Dangerous Goods on polation ernnental Industrial Hygienists ing Commercial Chemical Substances iemical Substances ision of the American Chemical Society) iation (USA) (ion System (USA) ISA, EU) it I Toxic cumulative lazard Category 2 irritation, Hazard Category 2B

- Disclaimer

The information set forth is based on information that ND Industries, Incorporated believes to be accurate. No warranty, expressed or implied, is intended. The information is provided solely for your information and consideration and ND Industries Inc. assumes no legal responsibility for use or reliance thereon. In the event of a discrepancy between the information on the non-English document and its English counterpart, the English version shall supersede.

®ND and ND Industries, Inc. are registered trademarks of ND Industries Incorporated, ®Vibra-TITE is a registered trademark of ND Industries, Inc.