

Safety Data Sheet
acc. to OSHA HCS

Printing date 07/17/2015

Reviewed on 05/22/2015

1 Identification**- Product identifier****- Trade name:** Stay-Put®**- Synonyms:** 107**- Part number:** SP107**- Relevant identified uses of the substance or mixture** Assembly aid / prevention of fastener slippage**- Details of the supplier of the safety data sheet****- Manufacturer/Supplier:**ND Industries, Inc
1000 North Crooks Road
Clawson, MI 48017
USA
Telephone: +1-248-288-0000
Email: info@ndindustries.com
Website: www.ndindustries.com**- Information department:** Product safety department**- Emergency telephone number:**

United States: 1-800-424-9300

International: +1-703-527-3887

2 Hazard(s) identification**- Classification of the substance or mixture**

GHS07

Acute Tox. 4 H302 Harmful if swallowed.

Acute Tox. 4 H312 Harmful in contact with skin.

Skin Irrit. 2 H315 Causes skin irritation.

Eye Irrit. 2A H319 Causes serious eye irritation.

Skin Sens. 1 H317 May cause an allergic skin reaction.

Flam. Liq. 4 H227 Combustible liquid.

- Label elements**- GHS label elements** The product is classified and labeled according to the Globally Harmonized System (GHS).**- Hazard pictograms**

GHS07

- Signal word Warning**- Hazard-determining components of labeling:**Acrylic ester
Polyglycol dioctanoate
Caprolactone Acrylate
N,N-dimethylacrylamide**- Hazard statements**H227 Combustible liquid.
H302+H312 Harmful if swallowed or in contact with skin.
H315 Causes skin irritation.
H319 Causes serious eye irritation.
H317 May cause an allergic skin reaction.**- Precautionary statements**P210 Keep away from flames and hot surfaces. – No smoking.
P261 Avoid breathing dust/fume/gas/mist/vapors/spray
P280 Wear protective gloves / eye protection / face protection.
P280 Wear protective gloves / protective clothing.
P264 Wash thoroughly after handling.
P305+P351+P338 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P301+P312 If swallowed: Call a poison center/doctor if you feel unwell.

Safety Data Sheet

acc. to OSHA HCS

Printing date 07/17/2015

Reviewed on 05/22/2015

Trade name: Stay-Put®

(Contd. of page 1)

P363 Wash contaminated clothing before reuse.
 P333+P313 If skin irritation or rash occurs: Get medical advice/attention.
 P337+P313 If eye irritation persists: Get medical advice/attention.
 P403+P235 Store in a well-ventilated place. Keep cool.
 P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

- Classification system:**- NFPA ratings (scale 0 - 4)****- HMIS-ratings (scale 0 - 4)****- Other hazards****- Results of PBT and vPvB assessment**

- **PBT:** Not applicable.
- **vPvB:** Not applicable.

3 Composition/information on ingredients

- Chemical characterization: Mixtures

- **Description:** Mixture of the substances listed below with nonhazardous additions.

- Dangerous components:

	Ethyl acrylate	20-30%
	Urethane acrylate	20-30%
	Acrylic ester	10-20%
	Caprolactone Acrylate	1-5%
2680-03-7	N,N-dimethylacrylamide	1-5%
18268-70-7	Polyglycol dioctanoate	1-5%
	Photochemical	1-5%
79-10-7	acrylic acid	1-5%
2530-83-8	Silane	1-5%
	Cross-linking agent	1-5%
67762-90-7	Synthetic amorphous silica (fumed)	1-5%

4 First-aid measures

- Description of first aid measures**- After inhalation:**

Supply fresh air and to be sure call for a doctor.
 In case of unconsciousness place patient stably in side position for transportation.
 Supply fresh air; consult doctor in case of complaints.

- **After skin contact:** Immediately wash with water and soap and rinse thoroughly.

- **After eye contact:** Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

- **After swallowing:** If symptoms persist consult doctor.

- Information for doctor:

- **Most important symptoms and effects, both acute and delayed** No further relevant information available.

- **Indication of any immediate medical attention and special treatment needed**

No further relevant information available.

5 Fire-fighting measures

- Extinguishing media**- Suitable extinguishing agents:**

CO₂, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

- **Special hazards arising from the substance or mixture** No further relevant information available.

- Advice for firefighters**- Protective equipment:**

Wear self-contained respiratory protective device.
 Wear fully protective suit.

(Contd. on page 3)

Safety Data Sheet

acc. to OSHA HCS

Printing date 07/17/2015

Reviewed on 05/22/2015

Trade name: Stay-Put®

(Contd. of page 2)

6 Accidental release measures

- Personal precautions, protective equipment and emergency procedures

Ensure adequate ventilation

Wear protective clothing.

- Environmental precautions: Do not allow to enter sewers/ surface or ground water.

- Methods and material for containment and cleaning up:

Ensure adequate ventilation.

Dispose of the collected material according to regulations.

- Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

7 Handling and storage

- Handling:

- Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace.

Prevent formation of aerosols.

- Information about protection against explosions and fires: Protect from heat.

- Conditions for safe storage, including any incompatibilities

- Storage:

- Requirements to be met by storerooms and receptacles: No special requirements.

- Information about storage in one common storage facility: Not required.

- Further information about storage conditions:

Keep receptacle tightly sealed.

Protect from heat and direct sunlight.

- Specific end use(s) No further relevant information available.

8 Exposure controls/personal protection

- Additional information about design of technical systems: No further data; see item 7.

- Control parameters

- Components with limit values that require monitoring at the workplace:

79-10-7 acrylic acid

REL Long-term value: 6 mg/m³, 2 ppm
Skin

TLV Long-term value: 5.9 mg/m³, 2 ppm
Skin

- Additional information: The lists that were valid during the creation were used as basis.

- Exposure controls

- Personal protective equipment:

- General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing.

Wash hands before breaks and at the end of work.

Avoid contact with the eyes and skin.

- Breathing equipment:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.

- Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

- Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

- Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

(Contd. on page 4)

Safety Data Sheet

acc. to OSHA HCS

Printing date 07/17/2015

Reviewed on 05/22/2015

Trade name: Stay-Put®

(Contd. of page 3)

- Eye protection:

Tightly sealed goggles

- Body protection: Protective work clothing

9 Physical and chemical properties

- Information on basic physical and chemical properties**- General Information****- Appearance:**

- **Form:** Viscous
- **Color:** Amber colored
- **Odor:** Characteristic
- **Odour threshold:** Not determined.

- pH-value: Not determined.**- Change in condition**

- **Melting point/Melting range:** Undetermined.
- **Boiling point/Boiling range:** 95 °C (203 °F)

- Flash point: 93 °C (199 °F)**- Flammability (solid, gaseous):** Not applicable.**- Ignition temperature:****- Decomposition temperature:** Not determined.**- Auto igniting:** Product is not selfigniting.**- Danger of explosion:** Not determined.**- Explosion limits:**

- **Lower:** Not determined.
- **Upper:** Not determined.

- Vapor pressure: Not determined.**- Density:** Not determined.

- **Relative density** Not determined.
- **Vapour density** Not determined.
- **Evaporation rate** Not determined.

- Solubility in / Miscibility with**- Water:** Not miscible or difficult to mix.**- Partition coefficient (n-octanol/water):** Not determined.**- Viscosity:**

- **Dynamic at 20 °C (68 °F):** 700 mPas
- **Kinematic:** Not determined.

- Solvent content:**- Organic solvents:** 0.0 %**- Solids content:** 42.0 %**- Other information** No further relevant information available.

10 Stability and reactivity

- Reactivity No further relevant information available.**- Chemical stability****- Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.**- Possibility of hazardous reactions** No dangerous reactions known.**- Conditions to avoid** No further relevant information available.**- Incompatible materials:** No further relevant information available.**- Hazardous decomposition products:** No dangerous decomposition products known.

(Contd. on page 5)

Safety Data Sheet

acc. to OSHA HCS

Printing date 07/17/2015

Reviewed on 05/22/2015

Trade name: Stay-Put®

(Contd. of page 4)

11 Toxicological information

- Information on toxicological effects

- Acute toxicity:

- LD/LC50 values that are relevant for classification:

Acrylic ester		
Oral	LD50	100 mg/kg (ATE)
Dermal	LD50	300 mg/kg (ATE)
Caprolactone Acrylate		
Oral	LD50	100 mg/kg (ATE)
Dermal	LD50	1100 mg/kg (ATE)
2680-03-7 N,N-dimethylacrylamide		
Oral	LD50	100 mg/kg (ATE)
18268-70-7 Polyglycol dioctanoate		
Oral	LD50	2500 mg/kg (rat)
79-10-7 acrylic acid		
Oral	LD50	250 mg/kg (rat)
Dermal	LD50	280 mg/kg (rabbit)
Inhalative	LC50/4 h	11 mg/l (ATE)
Cross-linking agent		
Oral	LD50	5000 mg/kg (rat)

- Primary irritant effect:

- **on the skin:** Irritant to skin and mucous membranes.

- **on the eye:** Irritating effect.

- **Sensitization:** Sensitization possible through skin contact.

- Additional toxicological information:

The product shows the following dangers according to internally approved calculation methods for preparations:
Irritant

- Carcinogenic categories

- IARC (International Agency for Research on Cancer)

79-10-7	acrylic acid	3
1333-86-4	Carbon black	2B

- NTP (National Toxicology Program)

None of the ingredients is listed.

- OSHA-Ca (Occupational Safety & Health Administration)

None of the ingredients is listed.

12 Ecological information

- Toxicity

- **Aquatic toxicity:** No further relevant information available.

- **Persistence and degradability** No further relevant information available.

- Behavior in environmental systems:

- **Bioaccumulative potential** No further relevant information available.

- **Mobility in soil** No further relevant information available.

- Additional ecological information:

- General notes:

Water hazard class 3 (Self-assessment): extremely hazardous for water

Do not allow product to reach ground water, water course or sewage system, even in small quantities.

Danger to drinking water if even extremely small quantities leak into the ground.

- Results of PBT and vPvB assessment

- **PBT:** Not applicable.

- **vPvB:** Not applicable.

- **Other adverse effects** No further relevant information available.

13 Disposal considerations

- Waste treatment methods

- **Recommendation:** Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

(Contd. on page 6)

Safety Data Sheet

acc. to OSHA HCS

Printing date 07/17/2015

Reviewed on 05/22/2015

Trade name: Stay-Put®

(Contd. of page 5)

- Uncleaned packagings:**- Recommendation:** Disposal must be made according to official regulations.**14 Transport information**

- UN-Number - DOT, ADN, IMDG, IATA	not regulated
- UN proper shipping name - DOT, ADN, IMDG, IATA	not regulated
- Transport hazard class(es) - DOT, ADN, IMDG, IATA - Class	not regulated
- Packing group - DOT, IMDG, IATA	not regulated
- Environmental hazards: - Marine pollutant:	No
- Special precautions for user	Not applicable.
- Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code	Not applicable.
- UN "Model Regulation":	not regulated

15 Regulatory information**- Safety, health and environmental regulations/legislation specific for the substance or mixture****- Sara****- Section 355 (extremely hazardous substances):**

None of the ingredients is listed.

- Section 313 (Specific toxic chemical listings):

79-10-7 acrylic acid

- TSCA (Toxic Substances Control Act):

N,N-dimethylacrylamide

Polyglycol dioctanoate

acrylic acid

Silane

Synthetic amorphous silica (fumed)

Carbon black

- Proposition 65**- Chemicals known to cause cancer:**

1333-86-4 Carbon black

- Chemicals known to cause reproductive toxicity for females:

None of the ingredients is listed.

- Chemicals known to cause reproductive toxicity for males:

None of the ingredients is listed.

- Chemicals known to cause developmental toxicity:

None of the ingredients is listed.

- Carcinogenic categories**- EPA (Environmental Protection Agency)**

None of the ingredients is listed.

- TLV (Threshold Limit Value established by ACGIH)

79-10-7 acrylic acid

A4

1333-86-4 Carbon black

A4

- NIOSH-Ca (National Institute for Occupational Safety and Health)

1333-86-4 Carbon black

- Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

(Contd. on page 7)

Safety Data Sheet

acc. to OSHA HCS

Printing date 07/17/2015

Reviewed on 05/22/2015

Trade name: Stay-Put®

(Contd. of page 6)

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- **Department issuing SDS:** ND Industries, Inc. - Safety, Health and Environmental Affaires

- **Contact:** Safety, Health and Environmental Affaires

- **Date of preparation / last revision** 07/17/2015 / -

- **Abbreviations and acronyms:**

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

ACGIH: American Conference of Governmental Industrial Hygienists

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

NFPA: National Fire Protection Association (USA)

HMIS: Hazardous Materials Identification System (USA)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

Flam. Liq. 4: Flammable liquids, Hazard Category 4

Acute Tox. 4: Acute toxicity, Hazard Category 4

Skin Irrit. 2: Skin corrosion/irritation, Hazard Category 2

Eye Irrit. 2A: Serious eye damage/eye irritation, Hazard Category 2A

Skin Sens. 1: Sensitisation - Skin, Hazard Category 1

- **Disclaimer**

The information set forth is based on information that ND Industries, Incorporated believes to be accurate. No warranty, expressed or implied, is intended. The information is provided solely for your information and consideration and ND Industries Inc. assumes no legal responsibility for use or reliance thereon. In the event of a discrepancy between the information on the non-English document and its English counterpart, the English version shall supersede.

®ND and ND Industries, Inc. are registered trademarks of ND Industries Incorporated,

®Vibra-TITE is a registered trademark of ND Industries, Inc.