

ND INDUSTRIES, INC. **1893 BARRETT ROAD** TROY, MICHIGAN 48084

(248) 288-0000 Fax: (248) 288-0022 24 hr. EMERGENCY CHEMTREC:

1-800-424-9300

**ND STRIP®** PRODUCT: MSDS ID: ND1022

ORIG. DATE: 3/01/93 **REV. DATE:** 

> **Chemical Safety** PREPARED BY:

SECTION I -Material Identification and Information

H: 0

F: 0

1/30/06

R: 0

**PPEB** 

**COMPONENTS** 

CAS #

**PERCENT** %

OSHA **ACGIH** PEL TLV

OTHER LIMITS RECOMMENDED

Nylon 6,6 (Polyhexamethylene adipamide)

32131-17-2

100

n.a.

n.a.

non-hazardous

Material and trace additives are not hazardous by 29 CFR 1910.1200

All ingredients are listed on the TSCA Inventory.

n.a.= not applicable / n.e.=not established

### **SECTION II -Physical and Chemical Characteristics**

BOILING POINT: n.a.

**VAPOR DENSITY:** n.a.

VOC #/gal. :

**VAPOR PRESSURE:** n.a.

**DENSITY OF COATING:** 

MELTING POINT: 250-265°C/482-509°F **SPECIFIC GRAVITY:** 1.13-1.15

**EVAPORATION RATE:** 

n.a.

WATER REACTIVE:

No. Insoluble.

**SOLUBILITY IN WATER:** 

air = 1

water = 1

APPEARANCE AND ODOR: Yellow rigid plastic with no apparent odor.

### **SECTION III - Fire and Explosion Hazard Data**

FLASH POINT: 752°F/400°C ASTM D-1929 **AUTOIGNITION TEMPERATURE:** not determined

UEL: FLAMMABILITY LIMITS % IN AIR: LEL: n.a.

**EXTINGUISHER MEDIA:** Water spray or any Class A extinguishing agent.

**SPECIAL FIREFIGHTING** PROCEDURES:

Wear a NIOSH approved self-contained breathing apparatus with full face piece operated in pressure-demand or other positive pressure mode when fighting fires. Fire fighting equipment should be decontaminated after use.

**UNUSUAL FIRE HAZARDS AND CONDITIONS TO** 

At temperatures above 644°F/340°C, heavy fuming, carbon dioxide, carbon monoxide, nitrogen oxides and hydrogen cyanide (660°F/349°F) will occur.

AVOID:

## MATERIAL SAFETY DATA SHEET

PRODUCT: ND STRIP®

### **SECTION IV - Reactivity Hazard Data**

STABILITY: stable: X unstable:

HAZARDOUS POLYMERIZATION: may occur: will not occur: χ

**CONDITIONS** Avoid temperatures at or above 340°C/644°F and open flame.

TO AVOID:

**INCOMPATIBILITY:** Avoid strong acids and oxidizing agents.

HAZARDOUS DECOMPOSITION PRODUCTS: At temperatures above 644°F/340°C, heavy fuming, carbon dioxide, carbon monoxide, nitrogen oxides and

hydrogen cyanide (660°F/349°F) will occur.

### SECTION V - Health Hazard Data

PRIMARY ROUTES OF ENTRY: INHALATION: X INGESTION: X SKIN ABSORPTION:

**EYE CONTACT:** Mechanical irritation only.

FIRST AID: Flush eyes with generous amounts of water for 15 minutes lifting both upper and lower eyelids occasionally. If

irritation occurs, seek medical attention.

**SKIN** Molten nylon will cause thermal burns.

**CONTACT:** 

If skin irritation develops, wash exposed area with soap and water. If irritation persists, seek medical attention. If

FIRST AID: molten polymer contacts skin, cool rapidly with cold water. Do not attempt to peel polymer from skin. Obtain

medical attention for thermal burns.

**INHALATION:** Material is not respirable.

FIRST AID: As supplied; not a significant hazard. Note: If fumes from combusted or overheated material are inhaled, remove

to fresh air. Seek medical attention if respiratory irritation occurs or if breathing becomes difficult.

**INGESTION:** Not a probable route of exposure.

**FIRST AID:** Seek medical consultation.

**CHRONIC** None known for solid state.

**EFFECTS:** Thermally decomposing or overheated material has been reported to be irritating to the mucous membranes and

respiratory tract.

Carcinogenic: None known.

# MATERIAL SAFETY DATA SHEET

**ND STRIP®** PRODUCT:

Component Oral LD50 **Dermal LD50** Inhalation LC50

n.a. Polyhexamethylene adipamide n.a. n.a.

### **SECTION VI - Control and Protective Measures**

RESPIRATORY Work in a well-ventilated. If grinding or machining parts particulate level should be kept below 15 mg/M3.

PROTECTION:

**PROTECTIVE** Wear protective gloves if working with molten polymer.

**GLOVES:** 

**EYE PROTECTION:** Wear NIOSH approved safety glasses at all times.

LOCAL EXHAUST: X MECHANICAL: SPECIFIC: VENTILATION

TO BE USED: OTHER (specify): Sufficient general area ventilation.

PROTECTIVE CLOTHING

Wear impervious clothing to prevent repeated, prolonged exposure.

AND EQUIPMENT:

**HYGIENIC WORK** Practice good personal hygiene. Wash hands before using restroom or eating.

PRACTICES:

### SECTION VII - Precautions for Safe Handling and Spill/Leak Procedures

### STEPS TO BE TAKEN IF MATERIAL IS SPILLED OR RELEASED:

Vacuum or sweep material into closed container suitable for disposal.

WASTE DISPOSAL

Landfill or incinerate in compliance with local, state and federal regulations.

**METHODS:** 

SAFE HANDLING Keep away from high temperatures and flame.

AND STORAGE:

OTHER PRECAUTIONS AND SPECIAL HAZARDOUS INFORMATION:

n.a.

RECOMMENDED HEALTH O FLAMMABILITY 0 REACTIVITY 0 NFPA/HMIS

PERSONAL В

**PROTECTION** 

note: ratings may differ according to application, environment, and physical state. RATING

# MATERIAL SAFETY DATA SHEET PRODUCT: ND STRIP® NOTES: Proper DOT Shipping Name: Not regulated

### **SECTION 313 SUPPLIER NOTIFICATION**

Detaching this notification from the Material Safety Data Sheet is prohibited by law and any copying or distribution of same requires this attachment be included.

This product contains the following toxic chemicals subject to the reporting requirements of section 313 of the Emergency Planning and Community Right-To-Know Act of 1986 and 40 CFR 372:

CAS # CHEMICAL NAME % BY WEIGHT

This material, but not necessarily the article into which it is incorporated, contains no toxic chemicals subject to the reporting requirements of section 313 of the Emergency Planning and Community Right-To-Know Act of 1986, 40 CFR 372.

This product contains the following materials that under California Proposition 65 of the Safe Drinking Water and Toxic Enforcement Act of 1986 are recognized to cause cancer or reproductive toxicity.

Material CAS # Concentration Cancer Reproductive cancer & Reproductive dagent Toxin

CAS # % Agent Toxin

None known.

ND Strip® is a registered trademark of ND Industries®, Inc.

The information contained herein is based on the data available to us and is believed to be correct. However, ND Industries®, Inc. makes no warranty, expressed or implied regarding the accuracy of these data or the results to be obtained from the use thereof. Information is supplied upon the condition that the persons receiving same will make their own determination as to its suitability for their properties prior to use. Since conditions of use are beyond our control, all risks are assumed by the user.