

ND INDUSTRIES , INC. 1893 BARRETT ROAD TROY, MICHIGAN 48084

(248) 288-0000 Fax: (248) 288-0022 24 hr. EMERGENCY CHEMTREC:

1-800-424-9300

PRODUCT: ND 750

MSDS ID: ND3179
ORIG. DATE: 10/21/2003

REV. DATE: 6/8/04

REV. DATE: PREPARED BY: Chemical Safety

SECTION I -Material Identification and Information H: 1 F: 1 R: 0 PPE: B

COMPONENTS		CAS #	PERCENT %	OSHA PEL	ACGIH TLV	OTHER LIMITS RECOMMENDED
Modified alkane resin	EX-12-255	mixture	25-35	n.e.	n.e.	
Modified Polyethylene	EX-12-308	Proprietary	15-25			
Filler	EX-12-73	1317-65-3	30-40	15 mg/m3	10 mg/m3	Nuisance dust
Modified turpene resin	EX-12-44	mixture	5-10	n.e.	n.e.	
Blowing agent	EX-12-55	80-51-3	5-10	n.e.	n.e.	
Synthetic hydrocarbon resin	EX-12-51	64741-88-4	2-4	5 mg/m3	5 mg/m3	
Pigment	EX-12-49	1333-86-4	<2	3.5 mg/m3	3.5 mg/m3	
Activator	EX-12-227	mixture	1-3	n.e.	n.e.	
Accelerator	EX-12-228	3006-93-7	<1.0	n.e.	n.e.	

The remaining components of this product are not considered hazardous substances or are below reportable levels under OSHA's Hazard Communication Standard (29 CFR 1910.1200)

All ingredients are listed on the TSCA Inventory.

n.a.= not applicable / n.e.=not established

SECTION II -Physical and Chemical Characteristics

BOILING POINT: n.a.

VAPOR DENSITY: n.a.

n.a.

air = 1

VOC :

DENSITY OF COATING:

MELTING POINT: n.a.

SPECIFIC GRAVITY:

1.22

water = 1

EVAPORATION RATE: n.a. WATER REACTIVE: n.a.

SOLUBILITY IN WATER:

Insoluble

APPEARANCE AND ODOR:

VAPOR PRESSURE:

Charcoal gray, puttylike solid with a slight rubber-like odor.

SECTION III - Fire and Explosion Hazard Data

FLASH POINT: >200° C

AUTOIGNITION TEMPERATURE: Not determined

FLAMMABILITY LIMITS % IN AIR: LEL: n.a. UEL: n.a.

EXTINGUISHER MEDIA: Fine water spray, Carbon dioxide, or foam.

SPECIAL FIREFIGHTING PROCEDURES: Full emergency equipment with self-contained breathing apparatus should be worn by firefighters. Irritating and toxic gases may be generated by thermal decomposition and combustion. Watch footing on floors and stairs for

EDURES: possible melting and spreading.

UNUSUAL FIRE HAZARDS AND CONDITIONS TO

Heavy water spray on molten material may scatter and spread fire.

AVOID:

MATERIAL SAFETY DATA SHEET

PRODUCT: ND 750

SECTION IV - Reactivity Hazard Data

STABILITY: stable: X unstable:

HAZARDOUS POLYMERIZATION: may occur: will not occur: X

CONDITIONS

Avoid Excessive heat.

TO AVOID:

INCOMPATIBILITY: Avoid strong oxidizing agents.

HAZARDOUS DECOMPOSITION PRODUCTS:

Depending on fire condition, the ingredients may produce Carbon monoxide, Carbon dioxide and other

combustible gases.

SECTION V - Health Hazard Data

PRIMARY ROUTES OF ENTRY: INHALATION: INGESTION: X SKIN ABSORPTION:

EYE CONTACT: In this form not likely.

FIRST AID: If particulate enters the eye, remove the particulate and flush with water.

SKIN Not applicable in solid form.

CONTACT:

FIRST AID:

INHALATION: Not applicable in solid form.

FIRST AID:

INGESTION: Not likely to occur in product form.

FIRST AID: If swallowed, get medical attention.

CHRONIC Not known

EFFECTS:

Carcinogenic: None of the components as present in the product are listed as carcinogenic.

MATERIAL SAFETY DATA SHEET

ND 750 PRODUCT:

Component

Modified alkane resin Modified Polyethylene

Filler

Modified turpene resin

Blowing agent

Synthetic hydrocarbon resin

Pigment Activator Accelerator Oral LD50

>4000 mg/kg (rat) none known not determined >10g/kg(rat) 2.3 g/kg (rat)

not determined not determined 5000 mg/kg (rat) 1370 mg/kg (rat) **Dermal LD50**

not determined none known not determined not determined >200 mg/kg (rabbit)

> not determined not determined non-toxic not determined

Inhalation LC50

not determined none known not determined 1,170 mg/m3/6 hr(rat) not determined not determined not determined non-toxic

0.055 mg/L/4 hr..(male rats)

SECTION VI - Control and Protective Measures

RESPIRATORY As supplied, not necessary.

PROTECTION:

PROTECTIVE

Not required

GLOVES:

EYE PROTECTION: Always wear safety glasses when working with material - Wear NIOSH approved safety glasses.

MECHANICAL:

LOCAL EXHAUST: **VENTILATION** TO BE USED:

OTHER (specify): n.a.

PROTECTIVE CLOTHING

As supplied, this product should not require protective clothing.

AND EQUIPMENT:

HYGIENIC WORK

Always practice good personal hygiene when working with chemicals and wash hands after using

SPECIFIC:

PRACTICES:

product.

SECTION VII - Precautions for Safe Handling and Spill/Leak Procedures

STEPS TO BE TAKEN IF MATERIAL IS SPILLED OR RELEASED:

Sweep up solid material and dispose of properly.

WASTE DISPOSAL

Dispose of material in accordance with local, state and federal regulations.

METHODS:

SAFE HANDLING AND STORAGE:

Avoid excessive heat.

OTHER PRECAUTIONS AND SPECIAL HAZARDOUS INFORMATION:

1

n.a.

RECOMMENDED NFPA/HMIS

RATING

HEALTH

FLAMMABILITY

REACTIVITY

PERSONAL

PROTECTION

В

note: ratings may differ according to application, environment, and physical state.

1

MATERIAL SAFETY DATA SHEET PRODUCT: ND 750 NOTES: DOT Shipping name: Not Regulated **SECTION 313 SUPPLIER NOTIFICATION** Detaching this notification from the Material Safety Data Sheet is prohibited by law and any copying or distribution of same requires this attachment be included. This product contains the following toxic chemicals subject to the reporting requirements of section 313 of the Emergency Planning and Community Right-To-Know Act of 1986 and 40 CFR 372: CHEMICAL NAME % BY WEIGHT none known This product contains the following materials that under California Proposition 65 of the Safe Drinking Water and Toxic Enforcement Act of 1986 are recognized to cause cancer or reproductive toxicity. Reproductive Cancer Reproductive cancer Concentration agent & Material CAS# Toxin Agent Toxin none known The information contained herein is based on the data available to us and is believed to be correct. However, ND Industries®, Inc. makes no warranty, expressed or implied regarding the accuracy of these data or the results to be obtained from the use thereof. Information is supplied upon the condition that the persons receiving same will make their own determination as to its suitability for their properties prior to use. Since conditions of use are beyond our control, all risks are assumed by the user.